



PHIFER

INCORPORATED

19 July 2012

LAFAYETTE VENETIAN BLINDS

Sent via E-mail: jrb@lafvb.com

Re: Flame Retardance of Phifer SheerWeave 4000 Products

PHIFER INCORPORATED certifies that the following material furnished by our firm:

Phifer SheerWeave Vinyl Coated Polyester: SheerWeave 4000, SheerWeave 4100, SheerWeave 4400, SheerWeave 4800 (All colors and weaves manufactured with FR-34 compound.)

is in compliance with the following standard(s):

1. Flammability per California Administrative Code, Title 19, Public Safety, Section 1237, Flame resistance Small Scale test, Registration Number F-44202.
2. National Fire Protection Association, NFPA No. 101, "Life Safety Code", Class "A" rating.
(Tested in accordance to ASTM E84.)
Flame Spread Index = 15 Smoke Developed Value = 300
3. International Building Code (IBC), Section 903.1, (Tested in accordance to ASTM E84), Class "A" rating.
4. NFPA 701, Standard Methods of Fire Test for Flame Propagation of Textiles and Films 2004 Edition - Test Method #1 (Small Scale).
5. NFPA 701, Standard Methods of Fire Tests for Flame Propagation of Textiles and Films 2010 Edition - Test Method #2 (Folded Specimens).
6. CAN/ULC-S109-03 Standard for Flame Tests of flame-Resistant Fabrics & Films Small Flame Test.
7. CAN/ULC-S109-03 Standard for Flame Tests of flame-Resistant Fabrics & Films Large Flame Test.
8. British Standard 5867: Part 2: 2008 Type B Performance Requirements.

If you have any questions or need further information, please contact me at 1-800-633-5955 Ext. 3075.

Sincerely,
PHIFER INCORPORATED

Keith Euerle
Director of Specialty Textiles Testing and Analysis